

NEW! | QUAD SERIES

JAB Quad Variable

AAdynTech's JAB Quad is the most powerful LED soft light in its class, consuming only 1,300 watts of power and outputting an amazing 120,000 lumens. The fixture, control box and connecting cable are rated IP65; weatherproof under any condition.

With a CRI of over 92, the JAB Quad creates a beautiful, even field of light in Daylight, Tungsten, or a Variable version that adjusts anywhere from 2800 Kelvin to 6000 Kelvin. Additionally, it has the capability of adding green or magenta to match any other white light fixture.

There are various ways to control the Quad; AAdynTech's User Interface Module, Wired DMX or Wireless DMX, making it very flexible for any kind of production.

Included with the fixture: Control Box, 14 Pin Control Cable, User Interface Module, Wireless Receiver, Standard Diffuser Lens, Twist Lock AC Cord, Yoke and Pin.

Accessories include: Travel Case, Lite Diffuser, Heavy Diffuser, Snap Grid, Chimera Pop Bank, Honeycomb Grid.

Like all AAdynTech products, the Quad is designed and manufactured in the United States by Sturdy Corporation, guaranteeing quality and dependable service.

92+
CRI

IP65
Rated



FEATURES AT A GLANCE:

- Minus/Plus Green/Magenta Correction
- 92+ CRI across entire brightness range
- Rated IP65
- 443 foot candle output @ 10 feet
- Color Range 2800k - 6000k
- Auto range voltage - 100/277 VAC-50/60Hz
- Low Power Consumption
Less than 15a @ 120Vac
- Flicker-free up to 260,000 fps
- Compatible with existing User Interface Modules (UIM)
- Wireless or wired DMX with RDM
- Daisy chain DMX
- Certified ETL, CSA, CE and RoHS compliant
- Operating temperature -20°C to +50°C
- Programmable multiple lightning and strobe effects
- 2 year warranty
- MSRP \$7000



JAB Quad Variable

NO DIFFUSER

	@10 FEET	@15 FEET	@20 FEET
Lux	4,768	2,217	1,313
Foot Candles	443	206	122

30° DIFFUSER

	@10 FEET	@15 FEET	@20 FEET
Lux	4,337	1,991	1,184
Foot Candles	403	185	110

55° DIFFUSER

	@10 FEET	@15 FEET	@20 FEET
Lux	3,573	1,668	1,001
Foot Candles	332	155	93

80° DIFFUSER

	@10 FEET	@15 FEET	@20 FEET
Lux	3,282	1,528	925
Foot Candles	305	142	86

SPECIFICATIONS

Control	Local, UIM, DMX
Source	LED, 2800k - 6000k CCT, 92+ CRI
Cooling	Passive
Mounting	Baby Pin or Junior
Certifications	ETL, CSA, CE and RoHS Compliant

FIXTURE DIMENSIONS

Length	617.2 mm	24.3 in
Width	150.9 mm	5.94 in
Height	474.5 mm	18.68 in
Weight	24.95 kg	55 lbs

CONTROL BOX DIMENSIONS





Length	390.0 mm	15.39 in
Width	188.4 mm	7.42 in
Height	314.2 mm	12.37 in
Weight	11.33 kg	25 lbs

POWER

Input Voltage	100-277v AC
Input Freq	50/60 Hz
Input Current	1300 Watts @ full

HIGHLIGHTS

- RoHS Compliant
- 500 foot candles @ 10 feet
- IP65 Rated
- Dimmable with no color shift
- No harmful UV or IR radiation



©2023 Sturdy Corporation. All rights reserved. As technical advancements continue, all specifications are subject to change without notice.